SIEMENS

## Data sheet for SIMOTICS S-1FK7

**Article No. :** **1FK7043-4CH71-1BG2**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 4,500 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 2.6 Nm |
| Rated current | 3.3 A |
| Static torque (60 K) | 2.90 Nm |
| Static torque (100 K) | 3.50 Nm |
| Stall current (60 K) | 3.30 A |
| Stall current (100 K) | 4.10 A |
| Moment of inertia | 1.000 kgcm² |
| Efficiency | 90.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.85 Nm/A |
| Voltage constant at 20° C | 54.0 V/1000*min⁻¹ |
| Winding resistance at 20° C | 1.20 Ω |
| Rotating field inductance | 13.6 mH |
| Electrical time constant | 11.30 ms |
| Mechanical time constant | 0.49 ms |
| Thermal time constant | 40 min |
| Shaft torsional stiffness | 11,400 Nm/rad |
| Net weight of the motor | 6.0 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | High Dynamic |
| Shaft height | 48 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP65 and DE flange IP67 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Plain shaft |
| Encoder system | Encoder AS24DQI: absolute encoder single-turn 24 bits |

| Optimum operating point | |
|---|---|
| Optimum speed | 4,500 rpm |
| Optimum power | 1.2 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 9,000 rpm |
| Max. permissible speed (inverter) | 9,000 rpm |
| Maximum torque | 10.0 Nm |
| Maximum current | 12.5 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 5 A |
| Maximum inverter current | 15 A |
| Maximum torque | 10.00 Nm |