SIEMENS

# Data sheet for SIMOTICS S-1FK7

## Article No. : 1FK7084-2AC71-1RB1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 2,000 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 15.0 Nm |
| Rated current | 6.7 A |
| Static torque (60 K) | 16.60 Nm |
| Static torque (100 K) | 20.00 Nm |
| Stall current (60 K) | 6.90 A |
| Stall current (100 K) | 8.50 A |
| Moment of inertia | 35.500 kgcm² |
| Efficiency | 93.0 % |

| Physical constants | |
|---|---|
| Torque constant | 2.36 Nm/A |
| Voltage constant at 20° C | 152.0 V/1000*min$^{-1}$ |
| Winding resistance at 20° C | 0.58 Ω |
| Rotating field inductance | 12.0 mH |
| Electrical time constant | 20.50 ms |
| Mechanical time constant | 1.02 ms |
| Thermal time constant | 55 min |
| Shaft torsional stiffness | 68,000 Nm/rad |
| Net weight of the motor | 21.3 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 80 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.050 mm |
| Concentricity tolerance | 0.10 mm |
| Axial runout tolerance | 0.10 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP65 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | with holding brake |
| Shaft end | Feather key |
| Encoder system | Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

| Optimum operating point | |
|---|---|
| Optimum speed | 2,000 rpm |
| Optimum power | 3.1 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 6,000 rpm |
| Max. permissible speed (inverter) | 3,800 rpm |
| Maximum torque | 61.0 Nm |
| Maximum current | 28.5 A |

| Holding brake | |
|---|---|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 22.0 Nm |
| Power supply voltage | DC 24 V ± 10 % |
| Coil current | 0.9 A |
| Opening time | 200 ms |
| Closing time | 60 ms |
| Highest braking work | 1,400 J |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 9 A |
| Maximum inverter current | 27 A |
| Maximum torque | 58.40 Nm |