SIEMENS

Data sheet 6AG1972-0BB12-2XA0

product type designation	**PROFIBUS connector**



SIPLUS DP PROFIBUS plug with R - with PG - 90 degrees based on 6ES7972-0BB12-0XA0 with conformal coating, -25…+70 °C, connection plug for PROFIBUS up to 12 Mbps, 90° cable outlet, terminating resistor with isolating function, with PG socket

product brand name	SIPLUS
Technical Product Detail Page	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
based on	6ES7972-0BB12-0XA0
mechanical data	
locking mechanism design	Screwed joint
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C
● in horizontal mounting position / during operation	70 ... -40 °C
● during storage and transport	70 ... -40 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
● with condensation / maximum	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
● conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
environmental category / according to IEC 60721 / note	* The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high reliability
type of coating	
● protection against pollution according to EN 60664-3	Yes; Type 1 protection
● for electronic devices in railway applications according to EN 50155	Yes; protective coating of the Class PC2 according to EN 50155:2023
type of test / of the coating / according to MIL-I-46058C	Yes; Discoloration of coating possible during service life

© Copyright Plcally

product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A

standards, specifications, approvals

resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to web page: selection aid TIA Selection Tool	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to website: Industrial communication	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to web page: SiePortal	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to website: Image database	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to website: CAx-Download-Manager	https://www.plcally.com/?s=6AG1972-0BB12-2XA0
● to website: Industry Online Support	https://www.plcally.com/?s=6AG1972-0BB12-2XA0

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.plcally.com/?s=6AG1972-0BB12-2XA0. (V4.7)

Approvals / Certificates

General Product Approval

CCC | CE EG-Konf. | Manufacturer Declaration | UKCA | China RoHS | UL

General Product Approval				EMV	For use in hazardous locations
EAC	China RoHS	CE EG-Konf.	UKCA	RCM	ATEX

For use in hazardous locations

IECEx | CCC-Ex

last modified: 3/10/2026

© Copyright Plcally