SIEMENS

## Data sheet 6AV2124-0XC24-0AX0

SIMATIC HMI TP2200 Comfort Pro, for support arm (not expandable, flange on top), Comfort Panel, touch operation, 22" widescreen TFT display, 16 million colors, PROFINET interface, MPI/PROFIBUS DP interface, 24 MB configuration memory, WEC 2013, configurable as of WinCC Comfort V14 SP1 with HSP



| | |
|---|---|
| **General information** | |
| Product type designation | TP2200 Comfort PRO |
| **Display** | |
| Design of display | TFT |
| Screen diagonal | 21.5 in |
| Display width | 475.2 mm |
| Display height | 267.3 mm |
| Number of colors | 16 777 216 |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 920 pixel |
| ● Vertical image resolution | 1 080 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 30 000 h |
| ● Backlight dimmable | Yes; 0-100 % |
| **Control elements** | |
| Keyboard | |
| ● Function keys | |
| — Number of function keys | 0 |
| — Number of function keys with LEDs | 0 |
| ● Keys with LED | No |
| ● System keys | No |
| ● Numeric keyboard | Yes; Onscreen keyboard |
| ● alphanumeric keyboard | Yes; Onscreen keyboard |
| Touch operation | |
| ● Design as touch screen | Yes; Projective-capacitive |
| Expansions for operator control of the process | |
| ● Direct keys (touch buttons as S7 input I/O) | 40 |
| **Installation type/mounting** | |
| Mounting | Support arm |
| Mounting position | vertical |
| Mounting in portrait format possible | No |
| Mounting in landscape format possible | Yes |
| maximum permissible angle of inclination without external ventilation | 35° |
| **Supply voltage** | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |


© Copyright Plcally

| | |
|---|---|
| **Input current** | |
| Current consumption (rated value) | 1.8 A |
| Starting current inrush I²t | 0.5 A²·s |
| **Power** | |
| Active power input, typ. | 44 W |
| **Processor** | |
| Processor type | X86 |
| **Storage** | |
| Flash | Yes |
| RAM | Yes |
| Memory available for user data | 24 Mbyte |
| **Type of output** | |
| Info LED | No |
| Power LED | No |
| Error LED | No |
| Acoustics | |
| ● Buzzer | No |
| ● Speaker | Yes |
| **Time of day** | |
| Clock | |
| ● Hardware clock (real-time) | Yes |
| ● Software clock | Yes |
| ● retentive | Yes; Back-up duration typically 6 weeks |
| ● synchronizable | Yes |
| **Interfaces** | |
| Number of industrial Ethernet interfaces | 2; 2 ports (switch) + independent port |
| Number of RS 485 interfaces | 1; RS 422 / 485 combined |
| Number of RS 422 interfaces | 0; together with RS 485 |
| Number of RS 232 interfaces | 0 |
| Number of USB interfaces | 2; USB 2.0 |
| Number of 20 mA interfaces (TTY) | 0 |
| Number of parallel interfaces | 0 |
| Number of other interfaces | 0 |
| Number of SD card slots | 2 |
| With software interfaces | No |
| Industrial Ethernet | |
| ● Industrial Ethernet status LED | 3 |
| ● Number of ports of the integrated switch | 2 |
| **Protocols** | |
| PROFINET | Yes |
| Supports protocol for PROFINET IO | Yes |
| IRT | Yes |
| PROFIBUS | Yes |
| EtherNet/IP | Yes |
| MPI | Yes |
| Protocols (Ethernet) | |
| ● TCP/IP | Yes |
| ● DHCP | Yes |
| ● SNMP | Yes |
| ● DCP | Yes |
| ● LLDP | Yes |
| WEB characteristics | |
| ● HTTP | Yes |
| ● HTTPS | Yes |
| ● HTML | Yes |
| ● XML | Yes |
| ● CSS | Yes |
| ● Active X | Yes |


© Copyright Plcally

| | |
|---|---|
| ● JavaScript | Yes |
| ● Java VM | No |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes |
| Further protocols | |
| ● CAN | No |
| ● MODBUS | Yes |
| **Interrupts/diagnostics/status information** | |
| Diagnoses | |
| ● Diagnostic information readable | Yes; S7 controller |
| **EMC** | |
| Emission of radio interference acc. to EN 55 011 | |
| ● Limit class A, for use in industrial areas | Yes |
| ● Limit class B, for use in residential areas | No |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| IP (rear) | IP65 |
| NEMA (front) | |
| ● Enclosure Type 4 at the front | Yes |
| ● Enclosure Type 4x at the front | Yes |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| **Ambient conditions** | |
| Suited for indoor use | Yes |
| Suited for outdoor use | No |
| Ambient temperature during operation | |
| Operation (vertical installation) | |
| — For vertical installation, min. | 0 °C |
| — For vertical installation, max. | 45 °C |
| Operation (max. tilt angle) | |
| — At maximum tilt angle, min. | 0 °C |
| — At maximum tilt angle, max. | 40 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Relative humidity | |
| ● Operation, max. | 90 %; no condensation |
| **Operating systems** | |
| proprietary | No |
| pre-installed operating system | |
| ● Windows CE | Yes; Windows Embedded Compact 2013 |
| **Configuration** | |
| Message indicator | Yes |
| Alarm system (incl. buffer and acknowledgment) | Yes |
| Process value display (output) | Yes |
| Process value default (input) possible | Yes |
| Recipe management | Yes |
| Configuration software | |
| ● STEP 7 Basic (TIA Portal) | No |
| ● STEP 7 Professional (TIA Portal) | No |
| ● WinCC flexible Compact | No |
| ● WinCC flexible Standard | No |
| ● WinCC flexible Advanced | No |
| ● WinCC Basic (TIA Portal) | No |


© Copyright Plcally

| | |
|---|---|
| ● WinCC Comfort (TIA Portal) | Yes; V14 SP1 HSP and higher |
| ● WinCC Advanced (TIA Portal) | Yes; V14 SP1 HSP and higher |
| ● WinCC Professional (TIA Portal) | Yes; V14 SP1 HSP and higher |
| **Languages** | |
| Online languages | |
| ● Number of online/runtime languages | 32 |
| Project languages | |
| ● Languages per project | 32 |
| **Functionality under WinCC (TIA Portal)** | |
| Libraries | Yes |
| Applications/options | |
| ● Web browser | Yes |
| ● Pocket Word | Yes |
| ● Pocket Excel | Yes |
| ● PDF Viewer | Yes |
| ● Media Player | Yes |
| ● SIMATIC WinCC Sm@rtServer | Yes |
| ● SIMATIC WinCC Audit | Yes |
| Number of Visual Basic Scripts | Yes |
| Task planner | |
| ● time-controlled | Yes |
| ● task-controlled | Yes |
| Help system | |
| ● Number of characters per info text | 320 |
| Message system | |
| ● Number of alarm classes | 32 |
| ● Bit messages | |
| — Number of bit messages | 6 000 |
| ● Analog messages | |
| — Number of analog messages | 200 |
| ● S7 alarm number procedure | Yes |
| ● System messages HMI | Yes |
| ● System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes |
| ● Number of characters per message | 80 |
| ● Number of process values per message | 8 |
| ● Acknowledgment groups | Yes |
| ● Message indicator | Yes |
| ● Message buffer | |
| — Number of entries | 1 024 |
| — Circulating buffer | Yes |
| — retentive | Yes |
| — maintenance-free | Yes |
| Recipe management | |
| ● Number of recipes | 500 |
| ● Data records per recipe | 1 000 |
| ● Entries per data record | 2 000 |
| ● Size of internal recipe memory | 4 Mbyte |
| ● Recipe memory expandable | Yes |
| Variables | |
| ● Number of variables per device | 4 096 |
| ● Number of variables per screen | 400 |
| ● Limit values | Yes |
| ● Multiplexing | Yes |
| ● Structures | Yes |
| ● Arrays | Yes |
| Images | |
| ● Number of configurable images | 750 |
| ● Permanent window/default | Yes |


© Copyright Plcally

| | |
|---|---|
| ● Global image | Yes |
| ● Pop-up images | Yes |
| ● Slide-in images | Yes |
| ● Image selection by PLC | Yes |
| ● Image number in the PLC | Yes |
| Image objects | |
| ● Number of objects per image | 600 |
| ● Text fields | Yes |
| ● I/O fields | Yes |
| ● Graphic I/O fields (graphics list) | Yes |
| ● Symbolic I/O fields (text list) | Yes |
| ● Date/time fields | Yes |
| ● Switches | Yes |
| ● Buttons | Yes |
| ● Graphic display | Yes |
| ● Icons | Yes |
| ● Geometric objects | Yes |
| Complex image objects | |
| ● Number of complex objects per screen | 40 |
| ● Alarm view | Yes |
| ● Trend view | Yes |
| ● User view | Yes |
| ● Status/control | Yes |
| ● Sm@rtClient view | Yes |
| ● Recipe view | Yes |
| ● f(x) trend view | Yes |
| ● System diagnostics view | Yes |
| ● Media Player | Yes |
| ● HTML browser | Yes |
| ● PDF display | Yes |
| ● IP camera display | Yes |
| ● Bar graphs | Yes |
| ● Sliders | Yes |
| ● Pointer instruments | Yes |
| ● Analog/digital clock | Yes |
| Lists | |
| ● Number of text lists per project | 500 |
| ● Number of entries per text list | 500 |
| ● Number of graphics lists per project | 500 |
| ● Number of entries per graphics list | 500 |
| Archiving | |
| ● Number of archives per device | 50 |
| ● Number of entries per archive | 50 000 |
| ● Message archive | Yes |
| ● Process value archive | Yes |
| ● Archiving methods | |
| — Sequential archive | Yes |
| — Short-term archive | Yes |
| ● Memory location | |
| — Memory card | Yes |
| — USB memory | Yes |
| — Ethernet | Yes |
| ● Data storage format | |
| — CSV | Yes |
| — TXT | Yes |
| — RDB | Yes |
| Security | |
| ● Number of user groups | 50 |
| ● Number of user rights | 32 |


© Copyright Plcally

| | |
|---|---|
| ● Number of users | 50 |
| ● Password export/import | Yes |
| ● SIMATIC Logon | Yes |
| Logging through printer | |
| ● Alarms | Yes |
| ● Report (shift log) | Yes |
| ● Hardcopy | Yes |
| ● Electronic print to file | Yes; PDF, HTML |
| Character sets | |
| ● Keyboard fonts | |
| — US English | Yes |
| Transfer (upload/download) | |
| ● MPI/PROFIBUS DP | Yes |
| ● USB | Yes |
| ● Ethernet | Yes |
| ● using external storage medium | Yes |
| Process coupling | |
| ● S7-1200 | Yes |
| ● S7-1500 | Yes |
| ● S7-200 | Yes |
| ● S7-300/400 | Yes |
| ● LOGO! | Yes |
| ● WinAC | Yes |
| ● SINUMERIK | Yes; With SINUMERIK option package as from WinCC V15 or higher |
| ● SIMOTION | Yes |
| ● Allen Bradley (EtherNet/IP) | Yes |
| ● Allen Bradley (DF1) | Yes |
| ● Mitsubishi (MC TCP/IP) | Yes |
| ● Mitsubishi (FX) | Yes |
| ● OMRON (FINS TCP) | No |
| ● OMRON (Host Link) | Yes |
| ● Modicon (Modbus TCP/IP) | Yes |
| ● Modicon (Modbus RTU) | Yes |
| ● OPC UA Client | Yes |
| ● OPC UA Server | Yes |
| Service tools/configuration aids | |
| ● Backup/Restore manually | Yes |
| ● Backup/Restore automatically | Yes |
| ● Simulation | Yes |
| ● Device switchover | Yes |
| **Peripherals/Options** | |
| Printer | Yes |
| SIMATIC HMI MM memory card: Multi Media Card | Yes; Up to 128 MB |
| SIMATIC HMI SD memory card: Secure Digital memory card | Yes; Up to 2 GB |
| SIMATIC HMI CF memory card Compact Flash Card | No |
| USB memory | Yes |
| SIMATIC IPC USB Flashdrive (USB stick) | Yes; Up to 16 GB |
| SIMATIC HMI USB stick | Yes; Up to 8 GB |
| Network camera | Yes |
| **Mechanics/material** | |
| Enclosure material (front) | |
| ● Plastic | No |
| ● Aluminum | Yes |
| ● Stainless steel | No |
| **Dimensions** | |
| Width of the housing front | 527 mm |
| Height of housing front | 330 mm; Without basic adapter |
| **Weights** | |
| Weight (without packaging) | 8.5 kg |


© Copyright Plcally

## Classifications

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-33-02-01 |
| eClass | 14 | 27-33-02-01 |
| eClass | 12 | 27-33-02-01 |
| eClass | 9.1 | 27-33-02-01 |
| eClass | 9 | 27-33-02-01 |
| eClass | 8 | 27-24-23-02 |
| eClass | 7.1 | 27-24-23-02 |
| eClass | 6 | 27-24-23-02 |
| ETIM | 10 | EC001412 |
| ETIM | 9 | EC001412 |
| ETIM | 8 | EC001412 |
| ETIM | 7 | EC001412 |
| IDEA | 4 | 6607 |
| UNSPSC | 15 | 43-21-15-06 |

## Approvals / Certificates

### General Product Approval




Manufacturer Declaration







Miscellaneous



### General Product Approval



China RoHS

### EMV



**last modified:** 4/4/2025


© Copyright Plcally