SIEMENS

Data sheet 6AV3688-3AY36-0AX0



SIMATIC HMI KP8 PN Key Panel, 8 short-stroke switches with multi-colored LEDs, PROFINET interfaces 8 configurable DI/DO pins, 24 V DC can be looped through parameterizable as of STEP 7 V5.5

General information	
Product type designation	KP8 PN
Control elements	
With parameterizable keys	Yes
Keyboard	
● Membrane keyboard	
— user-definable label membrane keys	Yes
● Function keys	
— Number of function keys	8
● Short-stroke keys	
— Number of short-stroke keys	8
Expansions for operator control of the process	
● DP direct LEDs (LEDs as S7 output I/O)	8; Adjustable brightness
● Number of color modes for LED	5; red, green, blue, yellow, white
● Direct keys (keys as S7 input I/O)	8
Installation type/mounting	
Mounting type	Clamp terminals
Mounting position	vertical
Rack mounting	No
Front mounting	Yes; Compatible with Extension Units dimensions
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Number of slots for command devices and signaling units	0
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; 24 V looped through at connector, no interruption on pulling
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.3 A
Digital inputs	
Number of digital inputs	8; Max. 8 inputs and outputs (total)
Input voltage	
● Rated value (DC)	24 V
Digital outputs	

© Copyright Plcally

Number of digital outputs	8; Max. 8 inputs and outputs (total)
Short-circuit protection	Yes
Switching capacity of the outputs	
● with resistive load, max.	100 mA
Output voltage	
● Rated value (DC)	24 V; Non-isolated
Total current of the outputs	
● Current per channel, max.	100 mA
● Current per group, max.	800 mA
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	
● Industrial Ethernet status LED	2; Per port
● Number of ports of the integrated switch	2; Per port
Protocols	
PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
PROFIsafe	No
PROFIBUS	No
EtherNet/IP	No
MPI	No
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
● TCP/IP	No
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
● AS-Interface Safety at Work	No
● CAN	No
● Data-Highway	No
● DeviceNet	No
● DeviceNet Safety	No
● Foundation Fieldbus	No
● INTERBUS	No
● INTERBUS-Safety	No
● Local Operating Network	No
● MODBUS	No
● SafetyBUS p	No
● SERCOS	No
● SUCOnet	No
● other bus systems	No
Test commissioning functions	
Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	Yes; Group 1, measured at a distance of 10 m
● Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
● Enclosure Type 4 at the front	No
● Enclosure Type 4x at the front	Yes; Incl. NEMA12

© Copyright Plcally

Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Suitable for safety functions	No
Use in hazardous areas	
● ATEX Zone 2	Yes
● ATEX Zone 22	Yes
● cULus Class I Zone 1	No
● cULus Class I Zone 2, Division 2	Yes
● FM Class I Division 2	Yes
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No
● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (Class NK)	No
● Polski Rejestr Statkow (PRS)	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Operation (vertical installation, portrait format)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	95 %; no condensation
Configuration	
Configuration software	
● STEP 7 Basic (TIA Portal)	Yes
● STEP 7 Professional (TIA Portal)	Yes
Functionality under WinCC (TIA Portal)	
Process coupling	
● S7-1200	Yes; with ET 200pro CPU and ET 200S CPU
● S7-1500	Yes
● S7-200	No
● S7-300/400	Yes; STEP 7 or SIMATIC STEP 7 Basic V11 or higher
● LOGO!	No
● WinAC	Yes
● SINUMERIK	No
● SIMOTION	No
● Allen Bradley (EtherNet/IP)	No
● Allen Bradley (DF1)	No
● Mitsubishi (MC TCP/IP)	No
● Mitsubishi (FX)	No

© Copyright Plcally

● OMRON (FINS TCP)	No
● OMRON (Host Link)	No
● Modicon (Modbus TCP/IP)	No
● Modicon (Modbus RTU)	No
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
● Aluminum	No
● Stainless steel	No
Service life	
● Short-stroke keys (in switching cycles)	1 500 000
● LEDs (ON period)	100 %
Dimensions	
Width of the housing front	98 mm
Height of housing front	155 mm
Mounting cutout, width	67.7 mm; Max. thickness of mounting plate 2 - 6 mm
Mounting cutout, height	129.7 mm
mounting depth	49 mm; Incl. angled SIMATIC Ethernet connector
Weights	
Weight (without packaging)	270 g

Classifications

	Version	Classification
eClass	16	27-33-02-04
eClass	14	27-33-02-04
eClass	12	27-33-02-04
eClass	9.1	27-33-02-04
eClass	9	27-33-02-04
eClass	8	27-24-23-05
eClass	7.1	27-24-23-05
eClass	6	27-24-23-05
ETIM	10	EC001415
ETIM	9	EC001415
ETIM	8	EC001415
ETIM	7	EC001415
IDEA	4	5266
UNSPSC	15	39-12-22-21

Approvals / Certificates

General Product Approval

General Product Approval	EMV	For use in hazardous locations			
China RoHS		FM			CCC-Ex

For use in hazardous locations	Maritime application

© Copyright Plcally

FM | ATEX | IECEx | Miscellaneous | CCC-Ex | ABS

Maritime application					
BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai	RINA	CCS (China Classification Society)

Maritime application	other	Industrial Communication
KR (Korean Register of Shipping)	PROFINET	PROFINET

last modified: 4/14/2025

© Copyright Plcally