SIEMENS

Data sheet 6ES7131-4BB01-0AA0



*** Spare part *** SIMATIC DP, 5 electronic modules for ET 200S, 2 DI Standard 24 V DC, 15 mm width, 5 units per packing unit

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	min. L+ (-0.5 V), under load
Output current	
● Rated value	500 mA
● permissible range, lower limit	0 mA
● permissible range, upper limit	500 mA
Power loss	
Power loss, typ.	0.4 W
Address area	
Address space per module	
● Address space per module, max.	1 byte
● with packing	2 bit
Digital inputs	
Number of digital inputs	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
● Type of input voltage	DC
● Rated value (DC)	24 V
● for signal "0"	-30 to +5 V
● for signal "1"	+15 to +30 V
Input current	
● for signal "1", typ.	7 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	2 ms; typically 3 ms
— at "0" to "1", max.	4.5 ms
— at "1" to "0", min.	2 ms; typically 3 ms
— at "1" to "0", max.	4.5 ms
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Encoder	

© Copyright Plcally

Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
● Group error SF (red)	No
● Status indicator digital input (green)	Yes; per channel
Potential separation	
Potential separation digital inputs	
● between the channels	No
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g

Classifications

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

Manufacturer Declaration

General Product Approval	EMV	For use in hazardous locations

China RoHS

For use in hazardous locations

© Copyright Plcally

FM	ATEX	UL	ATEX	IECEx	Miscellaneous

For use in hazardous locations	Maritime application				
CCC-Ex	ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai

Maritime application		
PRS	RINA	CCS (China Classification Society)

last modified: 7/1/2025

© Copyright Plcally