SIEMENS

Data sheet 6ES7138-4CF42-0AB0



Figure similar

*** Spare part *** SIMATIC DP, Power Module PM-E F PROFIsafe, f. ET200S; 24 V DC suitable for grounded setup relay for switching the voltage buses P1 and P2 up to Category 3 (EN 954-1)/ SIL2 (IEC61508)/PLD (ISO13849), can also be used in PROFINET configuration with IM 151-3 HF

Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	No
Input current	
From load voltage L+ (no load), typ.	100 mA
from backplane bus 24 V DC, max.	28 mA
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
● Inputs	5 byte
● Outputs	5 byte
Digital outputs	
Number of digital outputs	1; Relays
Short-circuit protection	No
Controlling a digital input	Yes
Switching capacity of the outputs	
● on lamp load, max.	100 W
Switching frequency	
● with resistive load, max.	2 Hz
● with inductive load, max.	0.1 Hz; with inductive load to IEC 60947-5-1, DC-13 / AC-15
● on lamp load, max.	2 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	10 A
— up to 55 °C, max.	8 A
— up to 60 °C, max.	7 A
vertical installation	
— up to 40 °C, max.	8 A
Relay outputs	
Switching capacity of contacts	
— with resistive load, up to 50 °C, max.	10 A
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnoses	
● Diagnostic information readable	Yes
● Wire break	No

© Copyright Plcally

● Short-circuit	Yes
● Missing load voltage	Yes
Diagnostics indication LED	
● Rated load voltage PWR (green)	Yes
● Group error SF (red)	Yes
● Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	No
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
Highest safety class achievable in safety mode	
● acc. to EN 954	4
● Performance level according to ISO 13849-1	e
● SIL acc. to IEC 61508	With Std-DO: Max. SIL 2, without Std-DO max. SIL 3 depending on configuration
Dimensions	
Width	30 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	80 g

Classifications

	Version	Classification
eClass	16	27-24-26-11
eClass	14	27-24-26-11
eClass	12	27-24-26-11
eClass	9.1	27-24-26-11
eClass	9	27-24-26-11
eClass	8	27-24-26-11
eClass	7.1	27-24-26-11
eClass	6	27-24-26-11
ETIM	10	EC002583
ETIM	9	EC002583
ETIM	8	EC002583
ETIM	7	EC002583
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

General Product Approval | **EMV** | **For use in hazardous locations** | **Functional Saftey**

China RoHS | FM | TUEV

© Copyright Plcally

Functional Saftey	Maritime application				
Type Examination Certificate	ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai

Maritime application
PRS

last modified: 7/17/2025

© Copyright Plcally