SIEMENS

Data sheet 6ES7144-4FF01-0AB0



SIMATIC DP, Electronic module for ET 200 PRO 4 AI U High Feature, +-10 V; 0...10 V; +-5 V; 1...5V; Channel diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Input current	
from supply voltage 1L+, max.	40 mA; Typical
from backplane bus 3.3 V DC, max.	12 mA; Typical
Encoder supply	
Number of outputs	4
Short-circuit protection	Yes; per module, electronic to frame
Output current	
● up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	1.1 W
Address area	
Address space per module	
● Address space per module, max.	8 byte
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	35 V
Cycle time (all channels) max.	5 ms
Input ranges (rated values), voltages	
● 0 to +10 V	Yes
● 1 V to 5 V	Yes
● -10 V to +10 V	Yes
● -5 V to +5 V	Yes
Cable length	
● shielded, max.	30 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	15 bit; 15 bit + sign at ±10 V, at ±5 V; 15 bit at 0 V to 10 V, at 1 V to 5 V
● Interference voltage suppression for interference frequency f1 in Hz	16,67 / 50 / 60 / 3 600
Smoothing of measured values	
● Parameterizable	Yes
● Step: None	Yes; 1x cycle time
● Step: low	Yes; 4x cycle time
● Step: Medium	Yes; 16x cycle time

© Copyright Plcally

● Step: High	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.0075 %
Temperature error (relative to input range), (+/-)	0.00075 %/K
Crosstalk between the inputs, min.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.004 %
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.075 %
Interference voltage suppression for f = n x (f1 +/- 0.5 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	60 dB
● Common mode interference (USS < 2.5 V), min.	80 dB; Interference voltage < 10 V
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes; Parameterizable
● Hardware interrupt	Yes; (limit value alarm), can be parameterized for channel 0
Diagnoses	
● Diagnostic information readable	Yes
● Wire break	Yes; at 1 to 5 V
● Short-circuit	Yes; at 1 to 5 V
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No
● between the channels and backplane bus	Yes
Permissible potential difference	
Between the inputs and MANA (UCM)	10 Vpp AC
Isolation	
Isolation tested with	707 V DC (type test)
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	150 g
Classifications	

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596

© Copyright Plcally

IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration | Metrological Approval

General Product Approval

China RoHS

Maritime application

NK / Nippon Kaiji Kyokai

Maritime application

CCS (China Classification Society) | KR (Korean Register of Shipping)

last modified: 10/23/2025

Subject to change without notice
© Copyright Plcally