SIEMENS

Data sheet 6ES7157-1AA00-0AB0

Siemens EcoTech

SIMATIC ET 200AL, PROFIBUS interface module IM 157-1 DP, degree of protection IP67; product phase-out planned - see SIOS 109989704



General information	
Product type designation	IM 157-1 DP
HW functional status	FS02
Firmware version	V1.0.x
Vendor identification (VendorID)	81A9H
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	STEP 7 V13 SP1 or higher
● STEP 7 configurable/integrated from version	From V5.5 SP4 Hotfix 3
● PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
Configuration control	
via dataset	Yes
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
● Rated value (DC)	24 V
● permissible range, lower limit (DC)	20.4 V
● permissible range, upper limit (DC)	28.8 V
● Reverse polarity protection	Yes; against destruction
Input current	
Current consumption (rated value)	50 mA
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Power loss	
Power loss, typ.	1.7 W
Address area	
Address space per station	
● Address space per station, max.	244 byte
Interfaces	
Number of PROFIBUS interfaces	1
1. Interface	
Interface type	PROFIBUS DP
Interface types	
● RS 485	Yes
● M12 port	Yes; 2x M12 B-coded

Subject to change without notice
© Copyright Plcally

Protocols	
● PROFIBUS DP device	Yes
Interface types	
RS 485	
● Transmission rate, max.	12 Mbit/s
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	No
PROFIBUS	Yes
EtherNet/IP	No
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV0	Yes
— DPV1	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● MAINT LED	Yes; Yellow LED
● Connection display DP	Yes; green LED
Potential separation	
between the load voltages	Yes
between PROFIBUS DP and all other circuit components	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; from FS01
Highest safety class achievable for safety-related tripping of standard modules	
● Performance level according to ISO 13849-1	PL d
● Category according to ISO 13849-1	Cat. 3
● SIL acc. to IEC 62061	SIL 2
● remark on safety-oriented shutdown	https://www.plcally.com/?s=6ES7157-1AA00-0AB0
Ambient conditions	
Ambient temperature during operation	
● min.	-30 °C
● max.	55 °C
Connection method	
Design of electrical connection for supply voltage	M8, 4-pole
ET-Connection	
● ET-Connection	M8, 4-pin, shielded
Dimensions	
Width	45 mm
Height	159 mm
Depth	46 mm
Weights	
Weight, approx.	211 g
Classifications	

	Version	Classification
eClass	16	27-24-26-08

© Copyright Plcally

eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval			Test Certificates	other	
	CE EG-Konf.	UKCA	Special Test Certific-ate	Miscellaneous	Confirmation

other		Environment	
Miscellaneous	产品合格 QC PASS	Environmental Con-firmations	Siemens EcoTech

last modified: 10/23/2025

Subject to change without notice
© Copyright Plcally