SIEMENS

Data sheet 6ES7193-6BN00-0NE0

SIMATIC ET 200SP, BaseUnit BU-SEND, for station expansion of ET 200SP via ET connection, WxH: 20 mmx117 mm

General information	
HW functional status	from FS04
Hardware configuration	
Slots	
● Number of slots	1
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	30 g

Classifications

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

CE EG-Konf. | UKCA | Manufacturer Declaration | UL | KC | RCM

General Product Approval	For use in hazardous locations

© Copyright Plcally

CCC-Ex FM

For use in hazardous locations				Maritime application
ATEX	Type Examination Certificate	Miscellaneous	CCC-Ex	RMRS

last modified: 2/1/2026

© Copyright Plcally