SIEMENS

Data sheet 6ES7193-6BP20-0BC1

Siemens EcoTech

SIMATIC ET 200SP, BaseUnit Type C1, BU20-P6+A2+4B BU type C1, Push-in terminals, with 2 AUX terminals, bridged to the left, WxH: 20 mmx117 mm



General information	
Product type designation	BU type C1
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	See manual
● For P1 and P2 bus	24 V
● For AUX bus	24 V; Equal potential group to P1/P2 bus or PE
● for process terminals	24 V
Rated value (AC)	See manual
● For P1 and P2 bus	230 V
● For AUX bus	230 V; Equal potential group to P1/P2 bus or PE
● for process terminals	230 V
Mains filter	
● integrated	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A; 10 A for process terminals 5 and 6
Hardware configuration	
Automatic encoding	Yes
Slots	
● Number of slots	1; Type C1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Standards, approvals, certificates	
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	0.873 kg
— global warming potential, (during production) [CO2 eq]	0.866 kg

Subject to change without notice
© Copyright Plcally

— global warming potential, (during operation) [CO2 eq]	0 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.0011 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Accessories	
Color coding labels	
● for process terminals	CC51
● for AUX terminals	CC84 to CC86
● for add-on terminals	does not exist
Connection method	
Terminals	
● Terminal type	Push-in terminal
● system-integrated shield connection	Yes; Optional
● Conductor cross-section, min.	0.14 mm²; AWG 26
● Conductor cross-section, max.	2.5 mm²; AWG 14
● Number of process terminals to I/O module	16; Pro slot
● Number of terminals to AUX bus	0
● Number of add-on terminals	0
● Number of terminals with connection to P1 and P2 bus	2; Pro slot
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	47 g

Classifications

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

© Copyright Plcally

Manufacturer Declaration

General Product Approval	For use in hazardous locations			
		FM	CCC-Ex	

For use in hazardous locations				Maritime application	
	Miscellaneous	Type Examination Certificate	CCC-Ex		

Maritime application					
		NK / Nippon Kaiji Kyokai			CCS (China Classification Society)

Maritime application	Environment
KR (Korean Register of Shipping)	

last modified: 2/1/2026

© Copyright Plcally