SIEMENS

Data sheet 6ES7194-3AA00-0AA0



SIMATIC DP, Connection block ECOFAST for ET 200ECO, 2x ECOFAST connections RS485, ID connector for PROFIBUS DP, Address setting

Power loss	
Power loss, typ.	2 W; The power loss depends on the current that you loop through via the connection block.
Dimensions	
Width	79 mm
Height	60 mm
Depth	30 mm
Weights	
Weight, approx.	313 g

Classifications

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

CE EG-Konf. UKCA Manufacturer Declaration UL RCM

General Product Approval	EMV	Maritime application

© Copyright Plcally

Maritime application

NK / Nippon Kaiji Kyokai



CCS (China Classification Society)

KR (Korean Register of Shipping)

last modified: 4/4/2025

Subject to change without notice
© Copyright Plcally