SIEMENS

Data sheet 6ES7194-4BA00-0AA0



SIMATIC DP, connection module for power module PM-E ET 200 Pro ECOFAST CU DP, 1x ECOFAST connection RS-485; product phase-out planned – see SIOS 109989704

Input current	
from load voltage 2L+ (without load), max.	10 A
Accessories	
Function description	Feeding of load voltage 2L+ within a station; 1x ECOFAST Cu
belongs to product	ET 200pro; PM-E DC24V
Dimensions	
Width	45 mm
Height	130 mm
Depth	60 mm
Weights	
Weight, approx.	125 g

Classifications

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

CE EG-Konf. UKCA Miscellaneous Manufacturer Declaration UL RCM

General Product Approval	Maritime application

Subject to change without notice
© Copyright Plcally

China RoHS

Maritime application

CCS (China Classification Society)

Maritime application

KR (Korean Register of Shipping)

last modified: 4/7/2025

© Copyright Plcally