SIEMENS

Data sheet 6ES7194-6KA00-0XA0

SIMATIC DP, Y cable for ET 200 distributed I/O For double connection of I/Os via single cable to ET 200 5-pole M12, 200mm



Figure similar

General information	
Product type designation	Y cable
Degree and class of protection	
IP degree of protection	IP67
Ambient conditions	
Ambient temperature during assembly, min.	-25 °C
Ambient temperature during assembly, max.	85 °C
Ambient temperature during storage/transportation	
● min.	-50 °C
● max.	80 °C
Cables	
Cable designation	Li9Y11Y 4x 0.34 mm²
Cable length	0.19 m
Color of core insulation of energy core	white / brown / blue / black
Mechanics/material	
Outgoing feeder type	180° cable outlet
Material of cable sheath	PUR
Material of core insulation	PP
Material property	
● Halogen-free	Yes
● Silicone-free	Yes

Classifications

	Version	Classification
eClass	16	27-24-22-20
eClass	14	27-24-22-20
eClass	12	27-24-22-20
eClass	9.1	27-24-22-20
eClass	9	27-24-22-20
eClass	8	27-24-92-05
eClass	7.1	27-24-92-05
eClass	6	27-24-92-05
ETIM	10	EC000237
ETIM	9	EC000237
ETIM	8	EC000237
ETIM	7	EC000237

© Copyright Plcally

IDEA	4	3553
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval	other	Environment
 	Confirmation	Environmental Confirmations

last modified: 4/7/2025

© Copyright Plcally