SIEMENS

## Data sheet 6ES7332-5HF00-0AB0



Figure similar

***spare part*** SIMATIC S7-300, analog output SM 332, isolated, 8 AO, U/I; diagnostics; resolution 11/12 bits, 40-pole, removing and inserting with active backplane bus possible

| | |
|---|---|
| **General information** | |
| Product function | |
| ● Isochronous mode | No |
| **Supply voltage** | |
| Load voltage L+ | |
| ● Rated value (DC) | 24 V |
| ● Reverse polarity protection | Yes |
| **Input current** | |
| from load voltage L+ (without load), max. | 340 mA |
| from backplane bus 5 V DC, max. | 100 mA |
| **Power loss** | |
| Power loss, typ. | 6 W |
| **Analog outputs** | |
| Number of analog outputs | 8 |
| Voltage output, short-circuit protection | Yes |
| Voltage output, short-circuit current, max. | 25 mA |
| Current output, no-load voltage, max. | 18 V |
| Output ranges, voltage | |
| ● 0 to 10 V | Yes |
| ● 1 V to 5 V | Yes |
| ● -10 V to +10 V | Yes |
| Output ranges, current | |
| ● 0 to 20 mA | Yes |
| ● -20 mA to +20 mA | Yes |
| ● 4 mA to 20 mA | Yes |
| Connection of actuators | |
| ● for voltage output four-wire connection | Yes |
| ● for current output two-wire connection | Yes |
| Load impedance (in rated range of output) | |
| ● with voltage outputs, min. | 1 kΩ |
| ● with voltage outputs, capacitive load, max. | 1 µF |
| ● with current outputs, max. | 500 Ω |
| ● with current outputs, inductive load, max. | 10 mH |
| Cable length | |
| ● shielded, max. | 200 m |
| **Analog value generation for the outputs** | |
| Integration and conversion time/resolution per channel | |
| ● Resolution with overrange (bit including sign), max. | 12 bit; ±10 V, ±20 mA, 4 mA to 20 mA, 1 V to 5 V: 11 bit + sign; 0 V to 10 V, 0 |


© Copyright Plcally

| | |
|---|---|
| | mA to 20 mA: 12 bit |
| ● Conversion time (per channel) | 0.8 ms |
| Settling time | |
| ● for resistive load | 0.2 ms |
| ● for capacitive load | 3.3 ms |
| ● for inductive load | 0.5 ms; 0.5 ms (1 mH); 3.3 ms (10 mH) |
| **Errors/accuracies** | |
| Operational error limit in overall temperature range | |
| ● Voltage, relative to output range, (+/-) | 0.5 % |
| ● Current, relative to output range, (+/-) | 0.6 % |
| Basic error limit (operational limit at 25 °C) | |
| ● Voltage, relative to output range, (+/-) | 0.4 % |
| ● Current, relative to output range, (+/-) | 0.5 % |
| **Interrupts/diagnostics/status information** | |
| Diagnostics function | Yes; Parameterizable |
| Substitute values connectable | Yes; Parameterizable |
| Alarms | |
| ● Diagnostic alarm | Yes; Parameterizable |
| Diagnoses | |
| ● Diagnostic information readable | Yes |
| Diagnostics indication LED | |
| ● Group error SF (red) | Yes |
| **Potential separation** | |
| Potential separation analog outputs | |
| ● between the channels | No |
| ● between the channels and backplane bus | Yes |
| ● Between the channels and load voltage L+ | Yes |
| ● between the channels and the power supply of the electronics | Yes |
| **Isolation** | |
| Isolation tested with | 500 V DC |
| **Connection method** | |
| required front connector | 40-pin |
| **Dimensions** | |
| Width | 40 mm |
| Height | 125 mm |
| Depth | 117 mm |
| **Weights** | |
| Weight, approx. | 272 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-01 |
| eClass | 14 | 27-24-22-01 |
| eClass | 12 | 27-24-22-01 |
| eClass | 9.1 | 27-24-22-01 |
| eClass | 9 | 27-24-22-01 |
| eClass | 8 | 27-24-22-01 |
| eClass | 7.1 | 27-24-22-01 |
| eClass | 6 | 27-24-22-01 |
| ETIM | 10 | EC001420 |
| ETIM | 9 | EC001420 |
| ETIM | 8 | EC001420 |
| ETIM | 7 | EC001420 |
| IDEA | 4 | 3562 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**


© Copyright Plcally

**General Product Approval**

Miscellaneous | Manufacturer Declaration | Metrological Approval

**General Product Approval** | **EMV**

China RoHS | Manufacturer Declaration

**For use in hazardous locations**

FM | Miscellaneous

**For use in hazardous locations** | **Maritime application**

CCC-Ex | NK / Nippon Kaiji Kyokai

**Maritime application**

CCS (China Classification Society)

**last modified:** 4/7/2025


© Copyright Plcally