SIEMENS

## Data sheet 6ES7361-3CA01-0AA0




Figure similar

***spare part*** SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

| | |
|---|---|
| **Supply voltage** | |
| Rated value (DC) | |
| ● 24 V DC | Yes |
| **Input current** | |
| from supply voltage L+, max. | 500 mA |
| **Power loss** | |
| Power loss, typ. | 5 W |
| **Hardware configuration** | |
| Number of interfaces per CPU, max. | 3 |
| **Dimensions** | |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 120 mm |
| **Weights** | |
| Weight, approx. | 505 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-08 |
| eClass | 14 | 27-24-22-08 |
| eClass | 12 | 27-24-22-08 |
| eClass | 9.1 | 27-24-22-08 |
| eClass | 9 | 27-24-22-08 |
| eClass | 8 | 27-24-22-08 |
| eClass | 7.1 | 27-24-22-08 |
| eClass | 6 | 27-24-22-08 |
| ETIM | 10 | EC001423 |
| ETIM | 9 | EC001423 |
| ETIM | 8 | EC001423 |
| ETIM | 7 | EC001423 |
| IDEA | 4 | 3564 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**

**General Product Approval**


© Copyright Plcally

Manufacturer Declaration

| General Product Approval | EMV | For use in hazardous locations | | | |
|---|---|---|---|---|---|
| Manufacturer Declaration | | | FM | | |

| For use in hazardous locations | | | Maritime application | | |
|---|---|---|---|---|---|
| | Miscellaneous | CCC-Ex | | | |

| Maritime application | | | | |
|---|---|---|---|---|
| | NK / Nippon Kaiji Kyokai | | | CCS (China Classification Society) |

**last modified:** 4/7/2025


Subject to change without notice
© Copyright Plcally