SIEMENS

Data sheet 6ES7792-0AA00-0XA0



Figure similar

*** spare part *** SIMATIC PG, USB external prommer

General information	
Design of the programming device	Desktop device
Display	
Design of display	without
Supply voltage	
Design of the power supply	12 V DC, 1.25 A (via power supply included 100 - 240 V / 50 - 60 Hz / 400 - 200 mA)
Ambient conditions	
Ambient temperature during operation	
● min.	5 °C
● max.	40 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Dimensions	
Width	172 mm
Height	40 mm
Depth	121 mm
Weights	
Weight, approx.	400 g
Classifications	

	Version	Classification
eClass	16	19-20-05-92
eClass	14	19-20-05-92
eClass	12	19-20-05-92
eClass	9.1	19-20-05-92
eClass	9	19-20-05-92
eClass	8	19-20-05-92
eClass	7.1	27-36-04-92
eClass	6	27-36-04-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	6628
UNSPSC	15	32-15-17-07

Subject to change without notice
© Copyright Plcally

Approvals / Certificates

General Product Approval





Manufacturer Declaration





General Product Approval	EMV





last modified: 5/22/2024

© Copyright Plcally